

Spectral functions on a quantum computer through system-environment interaction

Portability dossier - app

agQSL portability pipeline

2026-06-07

Field	Value
Slug	2026-arxiv-2605.01440-quantinum-h2-spectral-functions
Source	arXiv
Link	https://arxiv.org/abs/2605.01440
Category	app
Triaged	2026-05-16 by port_until_julien_parallel
Bootstrapped	2026-06-07

Contents

1	Source	3
1.1	Domain classification	3
1.2	Expert persona for Julien	3
1.3	Related prior work (brief bibliography)	3
1.4	Difficulty estimate	4
2	Extraction	5
2.1	What the paper does (one paragraph)	5
2.2	Quantum hardware used	5

2.3	Computational primitive	5
2.4	Resource fingerprint	6
2.5	Assumptions and results	7
2.6	Portability flags	7
2.7	Caveats	8
3	Portability matrix	9

1 Source

1.1 Domain classification

materials (condensed-matter quantum simulation). The paper computes ARPES spectral functions $A(k, \omega)$, the band-structure observable of solid-state physics, for one-dimensional fermionic lattice models. There is no distinct secondary application domain among the standard tags. The work is methodological (a quantum-simulation algorithm plus a hardware demonstration), and the “material” is a free-fermion chain chosen so that the 54-qubit result can be checked against exact simulation. Treat it as materials/condensed-matter with a strong algorithms-and-primitives flavour rather than a study of any specific compound.

1.2 Expert persona for Julien

A condensed-matter or quantum-simulation physicist fluent in dynamical correlation functions and spectral functions: retarded Green’s functions, the Lehmann representation, and how ARPES maps onto $A(k, \omega)$. Should be comfortable with digital simulation of fermionic lattice Hamiltonians (Jordan-Wigner encoding, Trotterised time evolution) and, importantly, with fermionic-Fourier-transform (FFFT) circuits and fermionic-SWAP / interleave networks, since the two-qubit-gate budget here is dominated by that machinery. Needs calibrated intuition about the shot-overhead versus gate-overhead tradeoff on trapped-ion hardware (Quantinuum H-series), so they can read off the stated gate counts, Trotter parameters, and infidelities and judge which numbers are device-specific.

1.3 Related prior work (brief bibliography)

- Verstraete, Cirac, Latorre, “Quantum circuits for strongly correlated quantum systems”, [arXiv:0804.1888](#) (PRA 79, 032316). Origin of the fermionic fast Fourier transform that is the reusable primitive at the centre of this work.
- Libbi, Rizzo, Tacchino, Marzari, Tavernelli, “Effective calculation of the Green’s function in the time domain on near-term quantum processors”, [arXiv:2203.12372](#) (PRR 4, 043038). Same observable (time-domain Green’s function / spectral function) on a superconducting processor via the dynamical-correlations route that this paper aims to undercut by a factor $\mathcal{O}(N)$ in shots; the natural baseline for a portability comparison.
- Quantinuum, “Digital quantum magnetism at the frontier of classical simulations”, [arXiv:2503.20870](#). Same vendor and same digital-simulation primitive (Trotterised lattice dynamics on the 56-qubit H2); already in our corpus, useful for calibrating H2 gate-fidelity expectations.
- Maskara et al., “Fast simulation of fermions with reconfigurable qubits”, [arXiv:2509.08898](#). The radix-2 interleave / fermionic-routing construction that this paper generalises to arbitrary radix, demonstrated on a different (neutral-atom) platform; a direct same-primitive, different-vendor pointer.
- Ferris, “Fourier transform for fermionic systems and the spectral tensor network”, [arXiv:1310.7605](#) (PRL 113, 010401). Background on the structure of the fermionic Fourier transform.

1.4 Difficulty estimate

medium. The full LaTeX source, figures, and supplemental material are in the dossier ([paper-source/](#)), so there is no paywall barrier, and the hardware fingerprint is stated explicitly in the main text: Quantinuum System Model H2-2, 54 qubits (27 system + 27 environment), Jordan-Wigner with alternating system/environment ordering, coupling $\epsilon = 0.5$, 10 Trotter steps at $dt = 0.5$, and 2172 two-qubit gates per free-fermion circuit (of which 1298 are the environment overhead), using the $\mathcal{O}(N \log^2 N)$ FFFT compilation. What lifts this above **low** is the exotic primitive stack: radix- n fermionic Fourier transform, fermionic-SWAP interleave networks, and a graph-decimation CZ compilation, plus reliance on the supplemental material for the explicit gate sequences and the finite- ϵ / strong-coupling analysis. Julien will need to read those primitives carefully to attribute the gate budget correctly, but nothing here is unreadable or missing.

2 Extraction

2.1 What the paper does (one paragraph)

The paper introduces a quantum-computing method to measure single-particle spectral functions $A(k, \omega)$, the ARPES band-structure observable, for one-dimensional fermionic lattice models, while avoiding the $\mathcal{O}(N)$ shot overhead of the usual dynamical-correlation route. Rather than measuring non-commuting operators such as $c_j + c_j^\dagger$ one site at a time, it couples the system to an auxiliary “environment” register of equal size (an idealised model of the photoemission process), evolves the joint system, and reads out the environment’s momentum-space occupation number $n(k)$, which is proportional to $A(k, \omega)$ at all momenta k for a chosen frequency ω in a single measurement setting. Reading $n(k)$ requires a fermionic Fourier transform (FFT), for which the authors give an arbitrary-radix construction plus an efficient fermionic-SWAP interleave. They demonstrate the method on Quantinuum’s H2-2 trapped-ion machine, computing $A(k, \omega)$ for a 27-site free-fermion chain using 54 qubits.

2.2 Quantum hardware used

- **Vendor / machine:** Quantinuum System Model H2 ion-trap computer. The spectral-function demonstration ran on H2-2; the FFFT benchmark (Fig. 3b) ran on both H2-1 and H2-2.
- **Qubit count:** 54 used for the spectral-function demonstration (27 system + 27 environment). The FFFT benchmark used 27 qubits. H2 exposes 56 qubits in total (vendor spec, not stated in the paper).
- **Connectivity:** effective all-to-all. The paper states ion traps “enjoy effective all-to-all connectivity” and its interleave compilation (Fig. 2 / Algorithm 2) is written “for all-to-all coupled architectures where SWAPs can be performed implicitly in software”. Substrate: QCCD ($^{171}\text{Yb}^+$ hyperfine qubits, ions shuttled between trap zones) per the vendor notes.
- **Gate set:** the paper builds circuits from fermionic-hopping / Givens-rotation gates $e^{i(X_i X_j + Y_i Y_j)\theta}$ with continuously tunable angle, plus S , Z single-qubit gates, and CZ / CX / CY Clifford two-qubit gates for the interleave networks. The paper does not name H2’s native entangler; the H-series native two-qubit gate is an arbitrary-angle ZZ (Mølmer-Sørensen family) entangler (vendor note, not paper-stated).
- **Notable features leveraged:** effective all-to-all connectivity with SWAPs resolved implicitly in software; low two-qubit gate infidelity and long shot time (the latter is the stated motivation for the shot-saving design). Mid-circuit measurement with feed-forward was tested as one of five FFFT interleave implementations but performed worst and was not used in the final demonstration.

2.3 Computational primitive

Trotterised Hamiltonian simulation (digital real-time evolution of a fermionic lattice Hamiltonian), with a fermionic Fourier transform (FFFT) as the central subroutine for both ground-state preparation and momentum-space readout. The algorithm is non-variational: a fixed circuit is run, not a parametrised circuit inside a classical optimisation loop.

2.4 Resource fingerprint

Metric	Value	Source (page / equation / SI)
Qubits (logical)	54 fermionic modes = 27 system + 27 environment ($N = 27$ sites)	Abstract; “Implementation of our protocol” section
Qubits (physical)	54 trapped-ion qubits on H2-2 (no error correction, so logical = physical). H2 has 56 available (vendor spec, not in paper)	“Implementation of our protocol” section; vendor note
Circuit depth	not reported for the 54-qubit spectral-function circuit. Two-qubit-gate depth of the 27-qubit FFFT benchmark circuits is plotted in Fig. 3c but no numeric value appears in the text	Fig. 3c (figure only)
2Q-gate count (total)	2172 two-qubit gates per free-fermion circuit, of which 1298 are environment overhead	“Comparison with dynamical correlations” section
Measurement shots	not reported (a $\sim 27\times$ shot saving versus the dynamical-correlation method is claimed, but no absolute shot count is given)	“Comparison with dynamical correlations” section
Classical loop iter.	none (non-variational). Fixed circuit of 10 Trotter steps at $dt = 0.5$, total evolution time $t = 5$, coupling $\epsilon = 0.5$	“Implementation of our protocol” section
Wall-clock runtime	not reported (only an $\mathcal{O}(N)$ relative runtime improvement is claimed)	“Comparison with dynamical correlations” section

Supporting circuit-construction numbers (not the demonstration totals): the FFT on $N = 2$ modes uses 2 two-qubit gates (F_2); on $N = 3$ modes it uses 6 (F_3). The method adds $2N$ extra two-qubit gates per Trotter step plus one extra FFFT (compiled with $\mathcal{O}(N \log^2 N)$ two-qubit gates) relative to the baseline.

2.5 Assumptions and results

- **Claim.** A faithful raw-hardware measurement of $A(k, \omega)$ for a 27-site free-fermion chain (54 qubits). Both spectral peaks at $\omega = 0$ remain visible “by several standard deviations”, and the band shape (hence effective mass and group velocity) is “effectively unbiased” despite an overall contrast loss. The method is claimed to need $\mathcal{O}(N)$ fewer shots than the dynamical-correlation approach; for this experiment specifically, a $\sim 27\times$ shot saving and a $\sim 11\times$ total-cost saving are quoted.
- **Error bars / noise assumptions.** Raw hardware data, with no error mitigation described beyond the choice of FFFT compilation (the $\log^2 N$ scheme of Constantinides et al. was selected after benchmarking five variants). Hardware noise attenuates the signal towards $1/2$ (the fully-depolarised value) and produces a roughly k -independent “noise floor”, consistent with single- and two-qubit-local errors. Algorithmic (not hardware) systematics: finite coupling ϵ and finite time t broaden bands by $\sim 1/t$ and create ghost bands with amplitude ratio $r = (t\epsilon/(2n\pi + t\epsilon))^2$; the chosen $\epsilon = 0.5$, $t = 5$ give $\epsilon t = 2.5 \lesssim \pi$, which keeps $r \lesssim 1/9$. Ten Trotter steps introduce a Trotter error, but the authors argue their observable stays non-negative (unlike the dynamical-correlation Fourier transform) because $n(k)$ is an occupation number.
- **Comparison to classical baseline.** The system is a free-fermion chain chosen precisely so the 54-qubit circuit is exactly classically simulable; the hardware output is benchmarked against the exact noiseless values (Fig. 4b,c). This is a verification demonstration, not a quantum-advantage claim. The baseline the method aims to beat is the alternative *quantum* method (dynamical correlations measured one site at a time), not a classical algorithm.

2.6 Portability flags

- **Relies on effective all-to-all connectivity at 54 qubits.** The interleave and $\log^2 N$ FFFT compilations resolve SWAPs implicitly in software and then optimise the residual CZ network (Algorithm 2; SI graph-decimation sequences). This presupposes all-to-all coupling. On a fixed-layout device (heavy-hex, square lattice, linear chain) the SWAPs become explicit, restoring the $\mathcal{O}(N^2)$ -gate / $\mathcal{O}(N)$ -depth local-FSWAP cost the authors explicitly contrast against. This is the central portability concern.
- **Doubles the qubit count.** $2N$ qubits for an N -site model (system + environment). The shot saving is bought with a $2\times$ width overhead and a two-qubit-gate overhead (1298 of 2172 gates here are environment overhead).
- **Native continuously-parametrised two-qubit gate assumed.** Time evolution uses $e^{i(X_i X_j + Y_i Y_j)\theta}$ hopping gates and the FFT uses the F_2 / F_3 blocks, all with arbitrary angle. These map directly to the H-series arbitrary-angle entangler but must be decomposed into 2-3 fixed-angle two-qubit gates (CNOT, CZ, \sqrt{i} SWAP) on platforms lacking a native arbitrary-angle entangler, inflating the two-qubit count.
- **Connectivity-specific CZ compilation.** The graph-decimation interleave sequences are hand-optimised CZ/CX/CY circuits

given explicitly for 9 and 27 qubits (SI). They are topology-dependent and would need re-synthesis for any other qubit count or hardware graph.

- **Mid-circuit measurement + feed-forward is optional, not required.** The measurement-and-feed-forward interleave (giving $\mathcal{O}(1)$ depth) was one of five tested variants; it performed worst here, so the final demonstration uses a purely unitary compilation. A portability analysis should treat MCM as a leveraged-if-available accelerator, not a hard requirement.
- **Value proposition is platform-specific.** The $\mathcal{O}(N)$ shot saving matters because ion-trap shot rate is slow; on fast superconducting samplers, where shots are cheap but connectivity is constrained, the trade-off shifts.

2.7 Caveats

- No access barrier: the full arXiv LaTeX source, figures, and Supplemental Material are present in `paper-source/`. Nothing was paywalled or unreachable.
- Numeric values for two-qubit-gate **depth** (Fig. 3c), **infidelity** (Fig. 3b bars), and the per-point spectral errors (Fig. 4) live only inside vector figure PDFs and are not restated in the text; they are reported as “not reported” in the text-extractable sense above. The figure PDFs were not OCR’d for numeric extraction.
- Absolute **shot count** and **wall-clock runtime** are not stated anywhere in the text; only relative ($\mathcal{O}(N)$, $\sim 27\times$, $\sim 11\times$) figures are given.
- The H2 “56 qubits available” figure is a vendor specification cross-checked against `vendor-notes/trapped_ion_qubits.tex`; the paper itself states only that 54 qubits were used.

3 Portability matrix